# Safety Data Sheet

Prepared according to Federal Register / vol. 77, No. 58/ Monday, March 26, 2012 / Rules and Regulations

# Section 1 - Company & Product Identification

Product Name: Isopropanol Grade A Product Code: TT-I-735A Trade Name: Isopropanol

#### Manufactured by:

Spectrum Coatings Laboratories, Inc. 217 Chapman Street Providence, RI 02905 ph:401-781-4847 fax:401-781-1075 web: spectrumcoatings.us email: paintman97@gmail.com

### **Emergency Contact Information:**

Daytime Information: 8:00am - 4:30pm EST 401-781-4847

24 Hour Emergency Contact: Chemtrec - 800-424-9300 International: +1 703-527-3887 Emergency Information Only

Product Use: Professional Industrial and Commercial Spray Painting Not recommended for: Commodity General Public Use

# Section 2 - Hazards Identification

#### GHS Ratings:

	Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)	
<u>GHS Ha</u>	zards			
	H225 Highly flammable liquid and vapour			
<u>GHS Pre</u>	ecautions			
	P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/all motorized electrical equipment being used in the area where this material is being handled Use only non-sparking tools Take precautionary measures against static discharge		
	P233			
	P240			
	P241			
	P242			
	P243			
	P280	es/protective clothing/eye protection/face protection		
	P303+P361+P353	IF ON SKIN (or hair): Rinse skin with water	Remove/Take off immediately all contaminated clothing. /shower	
P370+P378		In case of fire: Use CO2, Foam, or Chemical Extinguisher for extinction		
	P403+P235	ted place. Keep cool		
	P501	container to suitable waste stream in accordance with local, d international regulations.		

#### Signal Word: Danger



Section 3 - Composition/information on ingredients				
Chemical Name	CAS number	Weight Concentration %		
Isopropyl Alcohol	67-63-0	90.00% - 100.00%		

# Section 2 - First aid measures

4.1. Description of first aid measures

First-aid measures general: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing. IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If

irritation develops or persists, get medical attention. IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or

medical professional. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries:

Symptoms/injuries after inhalation:

Symptoms/injuries after skin contact:

Symptoms/injuries after eye contact:

Symptoms/injuries after ingestion:

Chronic symptoms:

# Section 5 - Firefighting measures

Flash Point: 12 C (53 F) LEL: 2.00

UEL: 12.00

5.1. Extinguishing media

Suitable extinguishing media: Carbon dioxide, Carbon Dioxide, Foam

5.2. Special hazards arising from the substance or mixture

Fire hazard: Explosion hazard: Reactivity:

5.3. Advice for firefighters

Firefighting instructions: Protection during firefighting:

# Section 6 - Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures General measures:Evacuate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Ventilate area. Keep upwind.

#### 6.1.1. For non-emergency personnel

Protective equipment: Wear Protective equipment as described in Section 8. Emergency procedures: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment: Methods for cleaning up:

### Section 7 - <u>Handling and storage</u>

**7.1. Precautions for safe handling** Precautions for safe handling:

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions:

Storage Temperature:

Section 8 - Exposure controls/personal protection				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Isopropyl Alcohol 67-63-0	PEL 400ppm - TWA VPEL 400ppm - TWA VPEL 500ppm - STEL	TLV 200ppm - TWA TLV 400ppm - STEL	Not Established	

#### 8.2. Exposure controls

**Appropriate engineering controls:** Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas. **Hand Protection:** Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296.Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

**Eye Protection:** Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

**Skin and body protection:** Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure **Respiratory Protection:** Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

### Section 9 - Physical and chemical properties

Odor NA

Boiling Range 80 to 84 °C

Specific Gravity (SG) 0.786

Lbs VOC/Gallon Less Water 6.56

Physical State Liquid

% Volume Volatile 100.00

Formula Lb / Gal 6.56

gms VOC/Liter Less Water 786

### Section 10 - Stability and reactivity

#### 10.1 Reactivity

- 10.2. Chemical stability
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products

STABLE

Avoid contact with; acetaldehyde, acids, chlorine, ethylene oxide, isocyanates, strong oxidizing agents, Do not use with aluminum equipment at temperatures above 120 F.

Oxides of carbon, such as carbon dioxide & carbon monoxide. Hazardous polymerization will not occur.

### Section 11 - Toxicological information

Mixture Toxicity Component Toxicity

skin contact: eye contact: ingestion: <b>kin Contact</b>	Eye Contact	Ingestion
eye contact:		
eye contact:		
eye contact:		
icity (repeated ex	(posure):	
, , , , ,	,	
itisation:		
ation:		
	itisation: icity (single expo	itisation: icity (single exposure): icity (repeated exposure):

Effects of Overexposure				
Eye Contact	Eye Contact Can cause eye irritation. Symptoms include stinging, tearing, redness, and swell of eyes.			
Skin Contact	May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.			
Ingestion	Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.			
Inhalation	Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symtoms usually occur at air concentrations higher than the recommended exposure limits.			
Symptoms of Exposure	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation, stomach or intestinal upset, irritation of the nose,throat & airways, central nervous system depression, high blood sugar, coma.			
Target Organ Effects	Target Organ EffectsThis material shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Overexposure to this material has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mil reversible kidney effects, blood abnormalities.			
Cancer Information	Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is NOT listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.			
CAS Number	Description	<u>% Weight</u>	Carcinogen Rating	

# Section 12 - Ecological information

No data available

**Component Ecotoxicity** 

### Section 13 - Disposal considerations

Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

# Section 14 - Transport information

<u>Agency</u>	Proper Shipping Name	<u>UN Number</u>	Packing Group	Hazard Class
DOT	Paint Related Material	1263	II	3

# Section 15 - Regulatory information

**Commonwealth of Massachusetts "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

New Jersey Worker and Community Right To Know Hazardous Substance List: The following substances appear on the New Jersey Right To Know Hazardous Substance List.

Isopropyl Alcohol 90 to 100 %

**Commonwealth of Pennsylvania Worker and Community Right-To-Know Act:** This product contains the following chemicals which appear on the Pennsylvania Hazardous Substance List: 67-63-0

Country

**Regulation** 

All Components Listed

EU Risk Phrases

#### Safety Phrase

All components of this product are listed on the TSCA Inventory or are exempt.

- None

### Section 16 - Other information


Author: BCS

#### Hazardous Material Information System (HMIS)





#### National Fire Protection Association (NFPA)



**NON-WARRANTY.** The information presented in this publication is based upon the research and experience Spectrum Coatings and its suppliers. No representation or warranty is made concerning the accuracy or completeness of the information presented in this publication. Spectrum Coatings makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Spectrum Coatings are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Spectrum Coatings shall in no event be liable for any special, incidental, or consequential damages.

**Reviewer Revision** 

Date Prepared: 6/18/2015